

深圳市超越世纪电子有限公司

2. 54mm Female Header, Dual Row, Raise it, Straight

SPECIFICATIONS

材质Material:

绝缘体 (Insulator): Polyester (UL94V-0)

Standard: PBT Black

接触件Contacts: Brass

接触电镀Contact Plating: Au or Sn over 30 μ" Ni

电气性能Electrical Characteristics:

接触电阻Contact Resistance:20mΩ Max.



绝缘电阻 Insulator Resistance: 1000M Ω Min.

耐电压Withstanding Voltage:AC 500V

额定电流Currrnt Rating:3 AMP

适用温度范围 Operating Temperature: -40°C to $+105^{\circ}\text{C}$

耐温性能Temperature resistancet:205℃±5℃, 3s-5s max



订购方法 How To Order

2.54排母	H	A	XX	M	T/A	G0	XXX
	Plastics Height H=12.00 mm (加高)	Material Type A=PBT B=Nylon-6T C=LCP D=Nylon-46	NO. of Positions Per Row 02 thru 40	S: Straight(180°) R: Right Angle(90°) M: S.M.T	T: TIN(镀锡) A: Aureate (镀金)	Contact Plating SN: Tin G0: Gold Flash G2: 5u" Gold G3: 10u" Gold G4: 15u" Gold G5: 30u" Gold S0: Gold Flash/Tin Standard: G0	Pin Lenght 8.5 Y型端子 L12.7

常规表达：型号（2.54排母座）-胶芯高度（H）-规格（2*XXP）-类型（M）-接触件镀层（XXU"）-尺寸（XXX）

* 其它要求的产品另外说明 Other requests's product on the other hand description